

TECHNICAL DATA SHEET

FLUXA TEST OIL 110

Test Oil

Product Description

- Odourless, clear test oil for magnetic particle testing
- Carrier medium for powders and oil-based concentrates
- No disturbing intrinsic fluorescence
- Excellent wetting properties

Product Specifications

- Application temperature: -10 °C to 60 °C
- Flash point: > 100 °C
- Viscosity (20 °C): 2.6 mm²/s
- Viscosity (38 °C): 3.8 mm²/s
- Density (20 °C): approx. 0.77 g/cm³
- 3 years minimum keeping time at room temperature

Approvals and Specifications

- Type-tested according to DIN EN ISO 9934-2
- SAE AMS 2641, ASTM E 1444, ASTM E 709, ASME Code Sec. V Art. 7, NAVSEA T9074-AS-GIB-010/271

Your Benefits

- Easy handling
- High testing security

For the Environment

- Odourless
- Free from hazardous substances



Packaging

- 10 l canister (order no.: 9041.2)
- 25 l canister (order no.: 9041.25)
- 200 l barrel (order no. 9041.9)

KARL DEUTSCH Pruef- und Messgeraetebau GmbH + Co KG · Otto-Hausmann-Ring 101 · 42115 Wuppertal · Germany
Phone +49 202 7192 0 · Fax +49 202 7192 123 · info@karldeutsch.de · www.karldeutsch.de

The Technical Data Sheet provides recommendations and possible examples. Obligations or liability cannot be derived therefrom. The information is based on our current knowledge and does not release the user from personal responsibility. The object conditions and product suitability must be checked professionally and appropriately. Take into account the information given in the Safety Data Sheet. We are happy to provide test samples for trials. Issue: 17 December 2024

KARL DEUTSCH