

# ECHOTRACE HT-170

## Ultrasonic Couplant

### Product Description

- Special couplant for high-temperature testing
- Viscous liquid with excellent sliding properties
- Prevents dripping
- Ideally suited for overhead work
- Free of nitrite

### Product Specifications

- Application range: -40 °C to 170 °C
- Suitable for ferrous and non-ferrous metals, as well as plastics
- Shelf life: 3 years
- Storage temperature: 5 °C to 45 °C

### Your Benefits

- Good skin compatibility
- Very good coupling properties

### For the Environment

- Label-free



### Packaging

- 100 ml tube (order no.: 9000.174)

KARL DEUTSCH Pruef- und Messgeraetebau GmbH + Co KG · Otto-Hausmann-Ring 101 · 42115 Wuppertal · Germany  
Phone +49 202 7192 0 · [info@karldeutsch.de](mailto:info@karldeutsch.de) · [www.karldeutsch.de](http://www.karldeutsch.de)

The Technical Data Sheet provides recommendations and possible examples. Obligations or liability cannot be derived therefrom. The information is based on our current knowledge and does not release the user from personal responsibility. The object conditions and product suitability must be checked professionally and appropriately. Take into account the information given in the Safety Data Sheet. We are happy to provide test samples for trials. Issue: 11 June 2026