

# ECHOTRACE

## Ultrasonic Couplant

### Product Description

- Coupling agent for ultrasonic testing with portable devices
- Prevents dripping
- Ideally suited for overhead work
- Contains corrosion protection
- Free of silicone and nitrite

### Product Specifications

- Application range: 0 °C to 80 °C
- Suitable for ferrous and non-ferrous metals, as well as plastics
- Free of corrosive components according to ASME CODE, Sec. V (sulphur and halogens < 250 ppm)
- Shelf life: 3 years
- Storage temperature: 5 °C to 45 °C

### Approvals and Specifications

- Corresponds to: DIN 25435-1

### Your Benefits

- Good skin compatibility
- Very good coupling properties

### For the Environment

- Lable-free
- Water-based gel
- Residue-free removal with water



### Packaging

- 100 ml tube (order no.: 9000.004)
- 0.5 litre bottle (order no.: 9000.003)
- 3 l bucket (order no.: 9000.001)
- 5 litre cubitainer (order no.: 9000.002)
- 200 litre drum (order no.: 9000.006)

KARL DEUTSCH Pruef- und Messgeraetebau GmbH + Co KG · Otto-Hausmann-Ring 101 · 42115 Wuppertal · Germany  
Phone +49 202 7192 0 · [info@karldeutsch.de](mailto:info@karldeutsch.de) · [www.karldeutsch.de](http://www.karldeutsch.de)

The Technical Data Sheet provides recommendations and possible examples. Obligations or liability cannot be derived therefrom. The information is based on our current knowledge and does not release the user from personal responsibility. The object conditions and product suitability must be checked professionally and appropriately. Take into account the information given in the Safety Data Sheet. We are happy to provide test samples for trials. Issue: 11 June 2026