

ECHOKOR LF

Corrosion Protection Agent

Product Description

- Corrosion protection agent for ultrasonic testing
- Both for manual testing as well as for automated testing with immersion or water jet coupling

Product Specifications

- Recommended concentration: 1:40 - 1:100 in water
- pH value (2.5 %): approx. 8.4
- Density (20 °C): approx. 1.1 g/cm³
- Corrosion protection: 2-4 weeks (indoor storage)
- 3 years minimum keeping time at room temperature

Your Benefits

- Particularly low-foaming for use in coupling agent circuits

For the Environment

- Label-free



Packaging

- 5 litre canister (order no.: 9028.002)
- 200 litre barrel (order no.: 9028.003)

KARL DEUTSCH Pruef- und Messgeraetebau GmbH + Co KG · Otto-Hausmann-Ring 101 · 42115 Wuppertal · Germany
Phone +49 202 7192 0 · Fax +49 202 7192 123 · info@karldeutsch.de · www.karldeutsch.de

The Technical Data Sheet provides recommendations and possible examples. Obligations or liability cannot be derived therefrom. The information is based on our current knowledge and does not release the user from personal responsibility. The object conditions and product suitability must be checked professionally and appropriately. Take into account the information given in the Safety Data Sheet. We are happy to provide test samples for trials. Issue: 14 July 2022