## **TECHNICAL DATA SHEET**

# **FLUXA Test Oil**

### **Product Description**

- Odourless, clear test oil for magnetic particle testing
- Carrier medium for powders and oil-based concentrates
- No disturbing intrinsic fluorescence
- Excellent wetting properties

#### **Product Specifications**

- Application temperature: -10 °C to 60 °C
- Flash point: > 65 °C
- Viscosity (20 °C): 2 mm<sup>2</sup>/s
- Density (20 °C): approx. 0.74 g/cm<sup>3</sup>
- 3 years minimum keeping time at room temperature

#### **Approvals and Specifications**

- Type-tested according to DIN EN ISO 9934-2
- SAE AMS 2641, ASTM E 1444, ASTM E 709, ASME Code Sec. V Art. 7

#### **Your Benefits**

- Easy handling
- High testing security

#### For the Environment

- Odourless
- Free from hazardous substances



#### - Packaging —

- 10 I canister (order no.: 9040.2)
- 200 | barrel (order no.: 9040.9)

KARL DEUTSCH Pruef- und Messgeraetebau GmbH + Co KG · Otto-Hausmann-Ring 101 · 42115 Wuppertal · Germany Phone +49 202 7192 0 · Fax +49 202 7192 123 · info@karldeutsch.de · www.karldeutsch.de

The Technical Data Sheet provides recommendations and possible examples. Obligations or liability cannot be derived therefrom. The information is based on our current knowledge and does not release the user from personal responsibility. The object conditions and product suitability must be checked professionally and appropriately. Take into account the information given in the Safety Data Sheet. We are happy to provide test samples for trials. Issue: 14 July 2022

